RESOLUTION NO. 22-273

A RESOLUTION AUTHORIZING THE CITY OF PORT ARTHUR SECTION 4A ECONOMIC DEVELOPMENT CORPORATION TO ENTER INTO A CONTRACT WITH HERNANDEZ OFFICE SOLUTIONS OF NEDERLAND, TEXAS FOR A COPIER LEASE FOR 63 MONTHS. IN THE AMOUNT OF \$2,414.76 ANNUALLY; \$12,677.49 OVER THE 63 MONTHS. FUNDS AVAILABLE IN EDC ACCOUNT NUMBER 120-80-625-5470-00-000-000.

WHEREAS, the Port Arthur Economic Development Corporation desires to lease a copier from Hernandez Office Solutions for 63 months as described in Exhibit "A" attached hereto; and

WHEREAS, said copier will be for the use of co-working members and tenants of The Press Building; and

WHEREAS, Chapter 271 of the Texas Local Government Code allows the participation in cooperative purchasing programs, such as BuyBoard Cooperative Purchasing Program ("BuyBoard") as an alternative to formal bid process; and

WHEREAS, the copier lease was obtained through Buy-Board approved vendor for the City of Port Arthur and was approved by the Port Arthur Economic Development Corporation Board of Directors at its regular board meeting on June 6, 2022.

NOW, THEREFORE, BE IT RESOLVED BY THE CITY COUNCIL OF THE CITY OF PORT ARTHUR:

- **Section 1.** That the facts and opinions in the preamble are true and correct.
- Section 2. That the City Council approves the lease of the copier for The Press Building as delineated in Exhibit "A" attached hereto.
- **Section 3.** That a copy of the caption of this Resolution be spread upon the Minutes of the City Council.

READ, ADOPTED AND APPROVED on this day of A.D., 2022, at a Meeting of the City Council of the City of Port Arthur, Texas, by the following vote:

| AYES: |
|---|
| Mayor Bartel; |
| Councilmembers Jones, Kinlaw, Marks, |
| Councilmembers Johns, Kinlaw, Marks, Mossis and Frank, |
| NOES: MONO - |
| ATTEST: Sherri Bellard, City Secretary |
| APPROVED: |
| Krystle Mueller, Interim CEO |
| APPROVED AS TO FORM: |
| 705- |
| Frank Garza AEDC Attorney |
| APPROVED AS, TO FORM: |
| Valecia R. Tizerio, Ciry Attorney |
| APPROVED AS TO AVAILABILITY OF FUNDS: |
| Kandy Daniel, Interim Finance Director |

Exhibit "A"



AUTHORIZED DEALER



SALES AGREEMENT

| Customer | Ship To: | | | Customer Bil | 1 10: | | | |
|--|--------------|-----------------|--|-------------------|---------------------|--------------------|--|--|
| Customer | Name: Po | rt Arthur EDC | | Customer Na | me: Port Arthur E | DC | | |
| Address: | 549 | 9 4th Street | | Address: | 501 Proctor S | 501 Proctor Street | | |
| City, State, Zip: Port Arthur, Texas 77640 | | | City, State, Zi | p: Port Arthur, 7 | Texas 77640 | | | |
| Contact: Jana Barnes | | | Contact: | Jana Barnes | | | | |
| Date Phone Number Fax Number 05/05/22 | | Fax Number | Em | nail Address | Customer P. O. # | | | |
| | | | jbarne | es@paedc.com | | | | |
| Quantity | Model | | Description | Serial Nun | nber Term: | Pricing: | | |
| 1 | C8170H2 | Xerox C817 | 0H2, 70 page per minute, | | 63 mo FMV: | \$201.23 | | |
| ĺ | ĺ | High capacity | trays, dual scan document | | | | | |
| ĺ | | processor, Pri | int/Copy/Scan/fax, Color copier, | | 48 mo. FMV: | \$269.23 | | |
| Ì | | Office Finsher | r. | | | | | |
| İ | | | | | Sale Price: | \$10,900.00 | | |
| j | | | | | | | | |
| | | | | | | | | |
| | | | | | j | į | | |
| | | | | | | | | |
| ' | ' | ! | | | ı | 1 | | |
| faintenand | | X No | ∐ | | Subtotal | | | |
| | | | ims, toners and supplies and determs and conditions. | | | 1 | | |
| kciudes pap Billing Fred | | monthly X | quarterly annually | | Tax | | | |
| ase Billing | | 27.00 for | 3,000 copies | | | ! | | |
| | • | | \$0.009 per copy; color billed | at \$ 0.05 p | Delivery | INCLUDED | | |
| verayes. | monochroi | ne billed at | 30.003 per copy, color billed | at 9 0.03 p | эег сору | | | |
| olor Copi | es wiil be b | illed at a cost | per copy. | | Total | | | |
| | | | | | | | | |
| ate 5/5/20 | 22 | | ı | | Leasing: | | | |
| | | | | | LEAF Leasing compan | v | | |
| ustomer S | Signature | | | | Lease Company | i | | |
| aotomor c | g.iataro | | | | | Monthly X | | |
| uetomor E | Printed Nan | ne | | Term | Payment | | | |
| ustomer r | -iiiiteu Nan | 110 | | 1 G1111 | i ayment | Quarterly Other | | |
| alaa Barrii | nnománák sz | | | ć 0F.00 | 7500 | | | |
| - | esentative | | | \$ 95.00 | ZERO Soverent | FMV | | |
| aney Hern | andez | | | Doc Fee | Down Payment | Purchase Option | | |

Xerox® AltaLink® Color Multifunction Printers

xerox"

C8130/C8135/C8145/C8155/C8170



AltaLink® C8100 Series Color Multifunction Printers are built on Xerox® ConnectKey® Technology. For more information, go to www.ConnectKey.com.

| | | | The company of the co | | |
|--|--|--|--|---|---|
| System Specification | AltaLink® C8130 | AltaLink® C8135 | AltaLink® C8145 | AltaLink® C8155 | AltaLink® C8170 |
| Speed ¹ | | | | | |
| Color/Black-and-White | Up to 30/30 ppm | Up to 35/35 ppm | Up to 45/45 ppm | Up to 55/55 ppm | Up to 70/70 ppm |
| Monthly Duty Cycle ² | Up to 90,000 pages | Up to 110,000 pages | Up to 200,000 pages | Up to 300,000 pages | Up to 300,000 pages |
| Hard Drive/Processor/ Memory | Minimum 128 GB SSD/ Optiona l: 500 GB HDD/Intel Atom® Quad Core 1.91 GHz/4 GB system memory (8 GB system memory AltaLink® C8170) | | | | |
| Connectivity | Ethernet 10/100/1000 Base-T, High-speed USB 2.0 direct print, Wi-Fi/Wi-Fi Direct with optional Xerox® Dual Band Wireless Kit, NFC, Bluetooth (iBeacon) | | | | |
| Controller Features | Unified Address Book, Remote Control Panel, Configuration Cloning, Fleet Orchestrator, Configuration Watchdog | | | | |
| Optional Controller | Xerox [®] EX-c C8100 Print Server Powered by Fiery [®] | | | | |
| Copy and Print | | | | | |
| Copy and Print Resolution | Copy: Up to 600 x 600 dpi; Pri | nt: Up to 1200 x 2400 dpl | | | |
| First-Print-Out Time (as fast as) | 5.7 seconds color/4.2 seconds b | olack-and-white | 4.9 seconds color/3.8 seconds black-and-white | 4.5 seconds color/3.2 seconds black-and-white | 3.8 seconds color/3.0 seconds black-and-white |
| First-Copy-Out Time (as fast as) (from platen/ warmed-up state) | 6.1 seconds color/4.5 seconds b | plack-and-white | 5.5 seconds color/4.4 seconds black-and-white | 4.7 seconds color/3.7 seconds black-and-white | 4.0 seconds color/3.2 seconds black-and-white |
| Page Description Language | Adobe® PostScript® 3™, Adobe® PDF, PCL® 5c/PCL® 6 | | | | |
| Print Features | Print from USB, Print from Cloud Repositories (Dropbox, OneDrive, and Google Drive), Encrypted Secure Print, Xerox® Earth Smart Driver Settings, Job Identification, Booklet Layout, Store and Recall Driver Settings, Bi-directional Real-time Status, Scaling, Job Monitoring, Application Defaults, Two-sided Printing (as default), Hold All Jobs, Long Sheet (Banner) Printing, Print Around, Print on Alternate Paper; Optional: Print from and Scan to Xerox® DocuShare® Go content management. | | | | |
| Mobile and Cloud Ready | | | | | |
| Mobile Connectivity | 1 | • | (802.11 b/g/n/ac), AirPrint (iOS) | | |
| Mobile Printing | AirPrint®, Mopria®, Xerox® Print Service (Android), @PrintByXerox App; Optional: Xerox® Workplace Mobile App (IOS/Android), AirPrint (IOS) including iBeacon (Bluetooth) | | | | |
| Mobile Scanning | AirPrint®, Mopria®; Optional: X | erox [®] Workplace Mobile App (iO | S/Andraid) | | |
| Mobile Apps and Xerox App Gallery | Automate everyday processes with apps that translate, redact, eSign, personalize print, convert, route, collaborate and communicate. Visit xerox.com/WorkplaceApps to find apps by industry or workflow. Software and services; Xerox® DocuShare® (xerox.com/ecm), XMPie® (xerox.com/XMPie). Xerox® Workplace Solutions (xerox.com/WorkplaceSalutions) | | | | |
| Xerox [®] Workplace Suite and Xerox [®] Workplace Cloud | Optional: Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud based-version (Workplace Cloud) of this solution. | | | | |


| Scan | |
|-------------------|---|
| Standard Features | Destinations: Scan to USB/Email/Network (FTP/SMB), HTTP, HTTPS, SFTP destinations; File Formats: PDF, PDF/A, JPEG, TIFF; Convenience Features: Scan Preview, Scan to Home, Searchable PDF, Single/Multi-Page PDF/TIFF, Password Protected PDF, Unified Address Book, Optical Character Recognition (OCR), Scan to Folder, 1-Touch Apps, TWAIN Support |
| Optional Features | Scan to Cloud Repositories (Dropbox, OneDrive, and Google Drive) ³ . Xerox ^a Scanning App for DocuShare ^a , other solutions available through various Xerox Business Innovation Partners at xerox.com/Software-Solutions, Print from and Scan to Xerox ^a DocuShare ^a Go content management |
| Fax | |
| Standard Features | Internet Fax, Fax Build Job, Network Server Fax Enablement, Fax Build Job |
| Optional Features | Walk-up Fax (one-line and two-line options available, includes LAN Fax, Direct Fax, Fax Forward to Email or SMB Share |
| Security | |
| Standard Features | 802.1x, IPsec, HTTPS, SFTP and Encrypted Email, McAfee® Embedded Control Whitelisting, Firmware Verification, McAfee® ePolicy Orchestrator®, McAfee Enterprise Security Manager®, LogRhythm SIEM®, Splunk SIEM®, Network Authentication, SNMPv3, SHA-256 Hash Message Authentication, TL51.171.271.3, Security Certificates utilizing ECDSA, Automatic Self-signed Certificate, Cisco® Identity Services Engine (ISE) integration, automated threat response through McAfee® DXL/Cisco® pxGrid integration, Local Authentication(Internal Database), FIPS 140-2.User Access and Internal Firewall, Port/IP/Domain Filtering, Audit Log, Access Control, User Permissions, Configuration Watchdog, TPM, Trusted Boot, Encrypted Storage Drive (AES 256-bit, FIPS 140-2), Job Level Encryption via HTTPS and Drivers, Signed Email Under evaluation for Common Criteria Certification (ISO 15408), Encrypted Secure Print |
| Optional Features | McAfee® Integrity Control, Smart Card Enablement Kit (CAC/PIV/.NET) ⁴ , Xerox® Integrated RFID Card Reader, Encrypted Hard Disk (AES 256-bit, FIPS 140-2) with Image Overwrite, Xerox® Workplace Cloud/Suite Print Management and Content Security; learn more at xerox.com/WorkplaceSolutions |
| Print Management | |
| Standard Features | Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email), Network Accounting Enablement |
| Optional Features | Xerox® Workplace Cloud/Suite, other network accounting solutions available through various Xerox Business Innovation Partners. Xerox® Virtual Print Management Service; learn more at xerox.com/PrintManagement |

Features and Accessories

Single-Pass Duplex Automatic Document Feeder (DADF)

saves time by simultaneously scanning both sides of two-sided documents with up to 270 impressions per minute (ipm).

PAPER INPUT



USER INTERFACE



Intuitive Tablet-like 10.1-inch
Color Touchscreen is customizable
and lets you perform tasks in just a
few taps. Try it out at
xerox com/AltaLink8105UI

INNOVATIVE TECHNOLOGIES



Xerox® Integrated RFID Card Reader (optional) adds card-based authentication with support for over 90 access cards.



Near Field Communication (NFC)
Tap-to-Pair allows users to tap their
mobile devices to the AltaLink® C8100
Series user panel and quickly connect
with the MFP.



Smart Proximity Sensor detects when users are nearby. It conserves energy during inactive periods and automatically activates the device when a user approaches.

Two 520-sheet Adjustable Trays (common with all configurations). Tray 1 handles media sizes up to 11.7 x 17 in./A3 and Tray 2 handles media sizes up to 12 x 18 in./SRA3.



Envelope Kit (optional — replaces Tray 1) provides feeding of up to 60 envelopes.



High Capacity Tandern Tray Configuration holds a total paper capacity of up to 3,140 sheets.

Four Tray Module Configuration (available for C8130/C8135) holds a total of up to 2,180 sheets.

Bypass Tray handles up to 100 sheets; Custom sizes: 3.5 x 3.9 to 12.6 x 52 in./89 x 98 mm to 320 x 1,320 mm.

High Capacity
Feeder (optional) holds
3,000 sheets of letter/A4
paper, increasing the
maximum paper capacity
to 6,140 sheets.



PAPER OUTPUT/FINISHERS



Office Finisher (optional) provides advanced finishing functions, optional crease/score and saddle-stitch booklet, making it capable of 60-page booklets (2 to 15 sheets).



Business Ready (BR) Finisher (optional) gives you advanced finishing functions at a great value.



C-Fold/Z-Fold Unit (optional) adds C-fold, Z-fold and Z-half-fold to the BR Finisher or BR Booklet Maker Finisher.



BR Booklet Maker Finisher (optional) creates 64-page saddle-stitched booklets (2 to 16 sheets).

LONG SHEET PRINTING

Long Sheet Feed Kit (optional) provides the ability to print up to 12.6 x 52 in./ 320 x 1,320 mm media.





Dual Offset Catch Tray (available when no finishers are installed; Single Offset Catch Tray with finishers).



Integrated Office Finisher (optional with C8130/C8135/ C8145/C8155) provides 500-sheet stacking and 50-sheet, 2-position stapling.



Convenience Stapler (optional) staples up to 50-sheets of 20 lb./75 gsm media.

| Device Specification | |
|-------------------------|---|
| Control Panel Languages | US English, International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian, Catalan, Arabic |
| Accessories | |
| Optional | High Capacity Feeder 3000 A4/Letter Envelope Tray (Replaces Tray 1) Harizontal Transport Kit BR (Business Ready) Finisher (requires Horizontal Transport Kit) BR Booklet Maker Finisher (requires Horizontal Transport Kit) C-fold/Z-fold Unit for BR Finisher or BR Booklet Maker Finisher Convenience Stapler (includes Work Surface*) Integrated Office Finisher (Availab e it AltaLink® C8130, C8135, C8145, C8155) ffice F sher B ok et Moker for Office Finisher Hole Punch (2/3, 2/4, Swedish) Office Finisher Smart Card Enablement Kit* Xerox® Ex-c C8100 Print Server Powered by Fiery® Walk-up Fax (One- or Two-line options, includes LAN Fax) Wi-Fi/Wi-Fi Direct with Dual Band Wireless Kit Bluetooth Kit McAfee® Integrity Control Enablement Kit USB Keyboard/Shelf Kit Xerox® Integrated RFID Card Reader Kit Unicode Font Kit Foreign Device Interface (Also known as Auxiliary Access Device) Interface for third-party access control devices, such as coin machines and card readers Long Sheet Feed Kit (banner printing) SOOGB HDD Scan To Cloud Enablement Kit |
| Electrical Requirements | AltaLink® C8130 AltaLink® C8135 AltaLink® C8145 AltaLink® C8155 AltaLink® C8170 |
| North America | Voltage: 110-127 VAC +/- 10% Voltage: 110-127 VAC +/- 10% Frequency: 50/60 Hz +/- 3 %, 15 A Frequency: 50/60 Hz +/- 3 %, 20 A |
| Europe | Voltage: 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 3 %, 10 A Voltage: 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 3 %, 10 A |

| evice Sp cifica on (con a | ed) | | · 大学 · · · · · · · · · · · · · · · · · · | | |
|--|---|---|---|---|---|
| Power Consumption | AltaLink® C8130 | AltaLink® C8135 | AltaLink® C8145 | AltaLink® C8155 | AltaLink® C8170 |
| Running (Average) | 115V: 576 watts 230V: 586 watts | 115V: 600.3 watts 230V: 595.8 watts | 115V: 717 watts 230V: 674 watts | 115V: 806 watts 230V: 760 watts | 115V: 929 watts 230V: 908 watts |
| Standby Mode | 115V: 67 watts 230V: 71 watts | 115V: 64 watts 230V: 70 watts | 115V: 71 watts 230V: 71 watts | 115V: 72 watts 230V: 70.3 watts | 115V: 91.1 watts 230V: 79 watts |
| Auto Off/Sleep Mode | 115V: 0.69 watts 230V: 0.71 watts (Default time to sleep mode = 0 minutes) | 115V: 0.69 watts 230V: 0.72 watts (Default time to sleep mode = 0 minutes) | 115V: 0.67 watts 230V: 0.71 watts (Default time to sleep mode = 0 minutes) | 115V: 0.67 watts 230V: 0.71 watts (Default time to sleep mode = 0 minutes) | 115V: 0.68 watts 230V: 0.75 watts (Default time to sleep mode = 0 minutes) |
| Warm-up (from Off) | As fast as 85 seconds | | | | |
| Recovery from Sleep | As fast as 4.5 seconds | | | | |
| Operating Environment | Tollies and the second | | | | |
| Required Temperature Range | 50 to 82° F/10 to 28° C | | | | |
| Required Relative Humidity | 15% to 85% | | | | |
| Sound Power Levels | Operating: 63.7/64.2 dB(A) Standby: 4.0/4.0 dB(A) | | Operating: 65.2/67.3 dB(A) Standby: 4.3/4.3 dB(A) | angunga, anduru | Operating: 70.4 dB(A) Standby: 4.3 dB(A) |
| Dimensions and Weight | | | | | |
| Bas C nfiguration | Width: 24.4 in./620 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 316 lb./143.1 kg | | | | Width: 24.4 in./620 mm Depth: 31.2 in./793 mm Height: 46 in./1,169 mm Weight: 352.1 lb/159.7 kg |
| Wi h In egrated Office Finisher (C8130, C8135, C8145, C8155) | Width: 32.2 in./819 mm Depth: 28.5 in./723 mm Height: 44.55 in./1,130 mm Weight: 340 lb./154.2 kg | | | | N/A |
| Ni Of ce Finisher with Booklet Maker) | Width: 47.5 in./1.207 mm Depth: 28.5 in./723 mm Height: 44.5 in./1.130 mm Weight: 402.3 lb./182.5 kg | | | | Width: 47.5 in./1207 mm Depth: 31.2 in./793 mm Height: 46 in./1,169 mm Weight: 439 lb./199 kg |
| Base Configuration wit Business Ready (BR) Finisher | Width: 55 in./1,395 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 412.3 lb/187 kg | | | | Width: 55 in./1,395 mm Depth: 31.2 in./723 mm Height: 46 in./1,169 mm Weight: 448.4 lb./203.4 kg |
| Base C n guration with BR Booklet Maker Finisher | Width: 59 in./1,496.3 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 449.7 lb./204 kg | | | | Width: 59 in./1,496.3 mm Depth: 31.2 in./723 mm Height: 46 in./1,169 mm Weight: 486.3 lb./220.6 kg |
| Base C n guration with BR Booklet Maker Finisher and C-fold/Z-fold Unit | Width; 64.3 in./1,632 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 560.6 lb/254.3 kg | | | | Width: 64.3 in./1,632 mm Depth: 31.2 in./723 mm Height: 46 in./1,169 mm Weight: 597.2 lb/270.9 kg |
| Base Config ration with BR Booklet Maker Finisher, -fold/Z-fold Unit and High Capacity Feeder | Width: 93 in./2,361 mm Depth: 28.5 in./723 mm Height: 44.5 ln./1.130 mm Weight: 628.8 lb./285.2 kg | | | | Width: 93 in./2,361 mm Depth: 31.2 in./723 mm Height: 46 in./1,169 mm Weight: 665.8 lb/302 kg |
| ystem Certifications/Regula | itory Compliance | 海市 の色世界以下 | | | |
| Certifications | To view the test ist of cert fic | t ons, go to xerox.com/Office(| Certifications | | |

| Paper Handling | AltaLink® C8130 | AltaLink* CB135 | AltaLink® C8145 | AltaLink® C8155 | AltaLink C8170 |
|-------------------------|---|--|-------------------------------------|----------------------------------|---|
| Single-Pass Duplex Auto | omatic Document Feeder (DA | DF) | | | |
| Capacity ⁵ | 130 sheets | | | | 250 sheets |
| Speed (Up to) | 82 ppm black-and-white 141 ipm black-and-white | | | | 135 ppm black-and-white and color (simplex) 270 ipm black-and-white and color (duplex) |
| Paper Sizes Sensed | 3.4 x 4.9 in. to 11.7 x 17 ii | n./85 x 125 mm to 297 x 432 m | nm | | |
| Weights | 16 lb. to 32 lb. bond/60 to | 128 gsm | | | |
| Bypass Tray (Standard) | 建 多等是3年20年 | | | | |
| Capacity ⁵ | 100 sheets | | | | |
| Sizes | Custom Sizes: 3.5 x 3.9 ii | n, to 12.6 x 52 in./89 x 98 mm t | o 320 x 1320 mm (SEF); Optio | nal: Long Sheet Feed Kit (Banner | Printing) |
| Weights | 16 lb. bond to 110 lb. cov | er/S2 to 300 gsm, Long sheets | /banners (>19 in./483 mm); 28 | 8lb Bond - 120lb Index/106 - 220 | gsm |
| Media Types | Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Reloaded Heavyweight Card Stock Heavyweight Card Stock Heavyweight Glossy Card Hole Punched Labels Letterhead Lightweight Card Stock Reloaded Lightweight Card Stock Reloaded Lightweight Gard Stock Relightweight Gard Stock Relightweight Gard Stock Relightweight Glossy Card Stock Reloaded Preprinted Recycled Transparencies Long Sheets/Banners: Card Stock Reloaded Lightweight Card Stock Reloaded Lightweight Card Stock Reloaded Lightweight Card Stock | Reloaded Stock Stock Reloaded Hoaded tock Lock Reloaded | | | |

Trays 1 and 2 (Standard)

Capacity⁵ 520 sheets each

Tray 1: Custom Sizes: 5.5×7.2 in. to 11.7×17 in./140 $\times 182$ mm to 297×432 mm (SEF) Tray 2: Custom Sizes: 5.5×7.2 in. to 12×18 in./140 $\times 182$ mm to SRA3 (SEF) Sizes

16 lb. bond to 110 lb. cover/52 to 300 gsm Weights

Media Types Bond Card Stock

Card Stock Reloaded Custom Envelopes Envelopes
Glossy Card Stock
Glossy Card Stock Reloaded
Heavyweight Card Stock
Heavyweight Card Stock Reloaded
Heavyweight Glossy Card Stock
Heavyweight Glossy Card Stock Reloaded
Hole Punched

Labels Letterhead Lightweight Lightweight Card Stock Lightweight Card Stock Reloaded Lightweight Glossy Card Stock Lightweight Glossy Card Stock Reloaded

Plain Plain-Reloaded Preprinted Recycled Transparencies

| Paper Handling (continued) | AltaLink® C8130 | AltaLink C8135 | AltaLink "C8145 | AltaLink® C8155 | AltaLink® C8170 |
|------------------------------------|--|---|-------------------|-----------------|-----------------|
| ruper runding (continued) | ATTAILME CO. C. | | | | |
| Capacity ⁵ | Tray 3: 520 sheets Tray 4: 520 sheets | | | | |
| Sizes | Trays 3 and 4: 5.5 x 7.2 ln. to | 12 x 18 in./140 x 182 mm to | SRA3 mm (SEF) | | |
| Weights | 16 lb. bond to 110 lb. cover/52 | 2 to 300 gsm | | | |
| Media Types | Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Reloaded Heavyweight Card Stock Heavyweight Card Stock Reloaded Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Lightweight Glossy Card Stock Lightweight Card Stock Reload Lightweight Card Stock Lightweight Glossy Card Stock Lightweight Glossy Card Stock Lightweight Glossy Card Stock Plain Plain-Reloaded Preprinted Recyded Transparencies | k k Reloaded ied | | | |
| Capacity ^s | Tray 3: 867 sheets Tray 4: 1,133 sheets | | | | |
| Sizes | 8.5 x 11 in./A4, JIS B5. Executi | | | | |
| Weights | 16 lb. bond to 110 lb. cover/5 | 2 to 300 gsm | | | |
| Media Types | Bond Card Stock Custom Glossy Card Stock Hole Punched Labels Letterhead Lightweight Card Stock Lightweight Glossy Card Stock Plain Preprinted | | | | |
| Capacitys | Up to 60 envelopes | | | | |
| Sizes | #10 Commercial (9.25 x 4.125 Custom Sizes: 3.9 x 5.8 in. to 6 | i in.)/Monarch, DL, C5 i,4 x 9,5 in./98 x 148 mm to 16 | 2 x 241 mm | | |
| Weights | 20 lb. to 24 lb. bond/75 to 90 | gsm | | | |
| Capacity ⁵ | 3,000 sheets | | | | |
| Sizes | Standard Sizes: 8.5 x 11 in. or | 7.25 x 10.5 in./A4 or B5 LEF | | | |
| Weights | 16 lb. bond to 110 lb. cover/52 | 2 to 300 gsm | | | |
| Device Total Capacity ^S | Four Tray Module: 2,180 sheet Four Tray Module with High Co High Capacity Tandem Tray M High Capacity Tandem Tray M | apacity Feeder: 5,180 sheets | ler: 6,140 sheets | | |

| Stacking Tray Capacity* Dual Offset Catch Trays to 250 sheets each left Side For sp 1 your Up 100 sheets Integrated Office Finisher (Option at with AltaLi, k** C8130/C8135/C8145/C8155) Stacking Tray Capacity* Stocking Tray Capacity* Stocking Tray Capacity* Stocking Tray Capacity* Stocking Tray Capacity* Sites 3.5 x 3.9 in. to 11.7 x 17 in./89 x 98 irrn to 297 x 432 irrn Weights Stapling Single/Dual Position Auto-Stapling: So sheets maximum: Leter/Av/85 size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Leter/Av/85 size sheets (less than 90 gsm or (2) 220 gsm covers) Office Finisher Optional) Stacking Tray Capacity* 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in/A4) Stacking Tray Capacity* So sheets maximum: Leter/Av/85 size sheets (less than 90 gsm or (2) 220 gsm covers) Office Finisher Optional) Stacking Tray Capacity* So sheets maximum: Leter/Av/85 size sheets (less than 90 gsm or (2) 220 gsm covers) Os sheets maximum: Leter/Av/85 size sheets (less than 90 gsm or (2) 220 gsm covers) So sheets maximum: Leter/Av/85 size sheets (less than 90 gsm or (2) 220 gsm covers) So sheets maximum: Leter/Av/85 size sheets (less than 90 gsm or (2) 220 gsm covers) So sheets maximum: Leter/Av/85 size sheets (less than 90 gsm or (2) 220 gsm covers) North America: 2/3-hole punch Downtet Make For Office Finishe (Score/Crease, Saddle-Stitch Staple) (Optional) Avided Stitch Stapling Solde Stitch Stapling Solde Stitch Stapling Solde Stitch Stapling Letter — 8.5 x 11 in/As SEF Tabloid — 11. x 17 in/As SEF Tabloid — 11. x 1 | |
|--|-----------------|
| Integrated Office F in sher (Option at with Altotal. k" CB130/CB135/CB145/CB155) Stacking Tray Capacity' Soo sheets of 20 lb. bond/80 gsm – 8.5 x 11 in/A4 or 250 sheets of 20 lb. bond/80 gsm – 11 x 17 in/A3 Sizes 3.5 x 3.9 in. to 11.7 x 17 in/89 x 98 mm to 297 x 432 mm 16 lb. bond to 110 lb. cover/52 to 300 gsm Single/Dual Position Auto-Stopling: So sheets maximum: Letter/Ar/B5 size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Letter/Ar/B5 size sheets (less than 90 gsm or (2) 220 gsm covers) Office Finisher (Optional) Stacking Tray Capacity' 2.000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in/A4) Stacking Tray Sizes 8.3 x 7.2 in. to 11.7 x 17 in/210 x 182 mm to 297 x 432 mm Weights 16 lb. bond to 110 lb. cover/52 to 300 gsm Multiposition Stapling So sheets maximum: Letter/Ar/B5 size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Letter/Ar/B5 size sheets (less than 90 gsm or (2) 220 gsm covers) Weights 16 lb. bond to 110 lb. cover/52 to 300 gsm Multiposition Stapling So sheets maximum: Letter/Ar/B5 size sheets (less than 90 gsm or (2) 220 gsm covers) North America: 213-hole punch Department of the Cover/Crease. Saddle-stitch Staple) (Optional) Gooklet Make for Office Finishe (Score/Crease. Saddle-stitch Staple) (Optional) Top Tray Capacity' Sizes Letter – 8.5 x 11 in/A4 SEF Legid – 8.5 x 11 in/A4 | |
| Stacking Tray Capacity' 500 sheets of 20 lb. bond/80 gsm – 8.5 x 11 in/A4 or 250 sheets of 20 lb. bond/80 gsm – 11 x 17 in/A3 Sizes 3.5 x 3.9 in, to 11.7 x 17 in/89 x 98 mm to 297 x 432 mm Weights 16 lb. bond to 110 lb. cover/52 to 300 gsm Single/Dual Postition Auto-Stopling: 50 sheets maximum: Leter/A4/B5 size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal/Tabloid/A3/B4 size sheets (less than 90 gsm or (2) 220 gsm covers) Office Finisher (Optional) Stacking Tray Capacity' 2.000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in/A4) Stacking Tray Sizes 8.3 x 7.2 in, to 11.7 x 17 in/210 x 182 mm to 297 x 432 mm Weights 16 lb. bond to 110 lb. cover/52 to 300 gsm Multiposition Stapling 50 sheets maximum: Leter/A4/B5 size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal/Tabloid/A3/B4 size sheets (less than 90 gsm or (2) 220 gsm covers) Hole Punch (Optional) North America: 2/3-hole punch Europe: 2/4-hole punch Diptomat: 4-hole 'Swedish' punch Booklet Make for Office Finishe (Score/Crease, Saddle-stitch Staple) (Optional) Top Tray Capacity' 40 booklets (2-15 sheets) per booklet — 20 lb/80 gsm or less) Sizes Letter — 8.5 x 11 in/A4 SEF Legal — 8.5 x 14 in/A3 SEF Tabloid — 11 x 17 in/A3 SEF Saddle-Stitch Stapling 1-15 sheets/6-0 page booklet 16 to 105 gsm Score/Crease 1-15 sheets/6-0 page booklet 16 to 105 gsm Score/Crease 1-15 sheets/6-0 page booklet 16 to 105 gsm Susiness Ready (BR) Finisher (Optional) Requires Horizontal Transport Kit) Copacity' Officeting Top Tray: 500 sheets unstapled or 100 sets (single-position staple) 8.5 x 11 in/A4 Sizes 3,9 x 5.8 in to 125 x 192 kin/100 x 148 mm x 320 x 488 mm for top tray | co de |
| Sizes 3.5 x 3.9 in. to 11.7 x 17 lin./89 x 98 mm to 297 x 432 mm Weights 16 lb. bond to 110 lb. cover/52 to 300 gsm Single/Dual Position Auto-Staphing: | |
| Stapling Single/Dual Position Auto-Stapling Single/Dual Position Single/Dua | |
| Stapling Single/Dual Position Auto-Stapling: So sheets maximum: Letter/Ad/B5 size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal/Tabloid/A3/B4 size sheets (less than 90 gsm or (2) 220 gsm covers) Office Finisher (Optional) Stacking Tray Capacity? 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in./A4) Stacking Tray Sizes 8.3 x 7.2 in. to 11.7 x 17 in./210 x 182 mm to 297 x 432 mm Weights 16 lb. bond to 110 lb. cover/52 to 300 gsm So sheets maximum: Letter/Ad/B5 size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal/Tabloid/A3/B4 size sheets (less than 90 gsm or (2) 220 gsm covers) North America: 2/3-hole punch Europe: 2/4-hole punch Optional: 4-hole "Swedish" punch Booklet Make for Office Finishe (Score/Crease, Saddle-stitch Staple) (Optional) Top Tray Capacitys 40 booklets (2-15 sheets per booklet — 20 lb./80 gsm or less) Sizes Letter — 8.5 x 11 in./A4 SEF Tabloid — 11 x 17 in./A3 SEF Tabloid — 11 x 17 in./B4 SEF Tabloid — 11 x 17 in./B3 SEF Tabloid — 11 x 17 in.,B3 | |
| Auto-Stopling: 50 sheets maximum: Letter/Au/BS size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal/Tabloid/A3/B4 size sheets (less than 90 gsm or (2) 220 gsm covers) Office Finisher (Optional) Stacking Tray Capacity* 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in:/A4) Stacking Tray Sizes 8.3 x 7.2 in. to 11.7 x 17 in:/210 x 182 mm to 297 x 432 mm Weights In lib. bond to 110 lb. cover/52 to 300 gsm Multiposition Stapling So sheets maximum: Letter/Au/BS size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Letter/Au/BS size sheets (less than 90 gsm or (2) 220 gsm covers) North America: 2/3-hole punch Europe: 2/4-hole punch Optional: 4-hole "Swedish" punch Europe: 2/4-hole punch Optional: 4-hole "Swedish" punch Booklet Make for Office Finishe (Score/Crease, Saddle-stitch Staple) (Optional) Top Tray Capacity* 40 booklets (2-15 sheets per booklet - 20 lb/80 gsm or less) Sizes Letter - 8.5 x 11 in:/Au SEF Legal - 8.5 x 14 in:/Ba SEF Tobloid - 11 x 17 in:/A3 SEF Saddle-Stitch Stapling 2-15 sheets/B-60 page booklet 16 lb. bond to 67 lb. bond/60 to 256 gsm 1-15 sheets/unstapled 18 lb. bond to 67 lb. bond/60 to 105 gsm Business Ready (8R) Finisher (Optional) (Requires Horizontal Transport Kit) Capacity' Offsetting Top Tray: 500 sheets Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position stapling) 11 x 17 in., 8,5 x 14 in/A3 or 200 sets (single-position staple) 8.5 x 11 in/A4 Sizes 3,9 x 5.8 in to 12.6 x 19.2 in/100 x 148 mm x 320 x 488 mm for top tray | |
| Stacking Tray Capacity ⁵ 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in./A4) Stacking Tray Sizes 8.3 x 7.2 in. to 11.7 x 17 in./210 x 182 mm to 297 x 432 mm Weights 16 lb. bond to 110 lb. cover/52 to 300 gsm Multiposition Stapling 50 sheets maximum: Legter/AA/B5 size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal/Tabloid/A3/B4 size sheets (less than 90 gsm or (2) 220 gsm covers) Hole Punch (Optional) North America: 2/3-hole punch Europe: 2/4-hole punch Optional: 4-hole "Swedish" punch Booklet Make for Office Finishe (Score/Crease, Saddle-stitch Staple) (Optional) Top Tray Capacity ⁵ 40 booklets (2-15 sheets per booklet – 20 lb./80 gsm or less) Sizes Letter – 8.5 x 11 in./A4 SEF Legal – 8.5 x 14 in./B4 SEF Tabloid – 11 x 17 in./A3 SEF Saddle-Stitch Stapling 2-15 sheets/8-60 page booklet 16 lb. bond to 67 lb. bond/60 to 256 gsm 1-15 sheets/unstapled 18 lb. bond to 28 lb. bond/60 to 105 gsm Business Ready (BR) Finisher (Optional) (Requires Horizontal Transport Kit) Capacity ⁵ Offsetting Top Tray: 500 sheets Stacking Stapling Tray: 3.000 sheets unstapled or 100 sets (dual or 4-position stapling) 11 x 17 in., 8.5 x 14 in./A3 or 200 sets (single-position staple) 8.5 x 11 in./A4 Sizes 3.9 x 5.8 in to 12.6 x 19.2 in/100 x 148 mm x 320 x 488 mm for top tray | AND DESCRIPTION |
| Stacking Tray Sizes 8.3 x 7.2 in. to 11.7 x 17 in./210 x 182 mm to 297 x 432 mm | (Table) |
| Weights 16 lb. bond to 110 lb. cover/52 to 300 gsm | |
| Multiposition Stapling Hole Punch (Optional) North America: 2/3-hole punch Europe: 2/4-hole punch Optional: 4-hole Punch (Optional) Booklet Make for Office Finishe (Score/Crease, Saddle-stitch Staple) (Optional) Top Tray Capacity ⁵ 40 booklets (2-15 sheets per booklet – 20 lb/80 gsm or less) Sizes Letter – 8.5 x 11 in/A4 SEF Legal – 8.5 x 14 in/B4 SEF Tabloid – 11 x 17 in/A3 SEF Saddle-Stitch Stapling 2-15 sheets/8-60 page booklet 16 lb. bond to 67 lb. bond/60 to 256 gsm 1-15 sheets/unstapled 18 lb. bond to 28 lb. bond/60 to 105 gsm Business Ready (BR) Finisher (Optional) (Requires Horizontal Transport Kit) Capacity ⁵ Offsetting Top Tray: 500 sheets Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position stapling) 11 x 17 in, 8.5 x 14 in./A3 or 200 sets (single-position staple) 8.5 x 11 in/A4 Sizes 3.9 x 5.8 in to 12.6 x 19.2 in/100 x 148 mm x 320 x 488 mm for top tray | |
| Hole Punch (Optional) North America: 2/3-hole punch Europe: 2/4-hole punch Optional: 4-hole "Swedish" punch Optional: 4-hole "Swedish" punch Optional: 4-hole "Swedish" punch Optional: 4-hole "Swedish" punch Top Tray Capacitys 40 booklets (2-15 sheets per booklet – 20 lb/80 gsm or less) Sizes Letter – 8.5 x 11 in./A4 SEF Legal – 8.5 x 14 in./B4 SEF Tabloid – 11 x 17 in./A3 SEF Saddle-Stitch Stapling 2-15 sheets/8-60 page booklet 16 lb. bond to 67 lb. bond/60 to 256 gsm Score/Crease 1-15 sheets/unstapled 18 lb. bond to 28 lb. bond/60 to 105 gsm Business Ready (BR) Finisher (Optional) (Requires Horizontal Transport Kit) Capacitys Offsetting Top Tray: 500 sheets Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position stapling) 11 x 17 in., 8.5 x 14 in./A3 or 200 sets (single-position staple) 8.5 x 11 in./A4 Sizes 3.9 x 5.8 in to 12.6 x 19.2 in/100 x 148 mm x 320 x 488 mm for top tray | |
| Europe: 2/4-hole punch Optional: 4-hole "Swedish" punch Booklet Make for Office Finishe (Score/Crease, Saddle-stitch Staple) (Optional) Top Tray Capacitys 40 booklets (2-15 sheets per booklet – 20 lb/80 gsm or less) Sizes Letter – 8.5 x 11 in/A4 SEF Legal – 8.5 x 14 in/B4 SEF Tabloid – 11 x 17 in/A3 SEF Saddle-Stitch Stapling 2-15 sheets/8-60 page booklet 16 lb. bond to 67 lb. bond/60 to 256 gsm Score/Crease 1-15 sheets/unstapled 18 lb. bond to 28 lb. bond/60 to 105 gsm Business Ready (BR) Finisher (Optional) (Requires Horizontal Transport Kit) Capacitys Offsetting Top Tray: 500 sheets Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position stapling) 11 x 17 in., 8.5 x 14 in./A3 or 200 sets (single-position staple) 8.5 x 11 in./A4 Sizes 3.9 x 5.8 in to 12.6 x 19.2 in/100 x 148 mm x 320 x 488 mm for top tray | |
| Top Tray Capacity ⁵ 40 booklets (2-15 sheets per booklet – 20 lb/80 gsm or less) Letter – 8.5 x 11 in/A4 SEF Legal – 8.5 x 14 in/B4 SEF Tabloid – 11 x 17 in/A3 SEF Saddle-Stitch Stapling 2-15 sheets/8-60 page booklet 16 lb. bond to 67 lb. bond/60 to 256 gsm Score/Crease 1-15 sheets/unstapled 18 lb. bond to 28 lb. bond/60 to 105 gsm Business Ready (BR) Finisher (Optional) (Requires Horizontal Transport Kit) Capacity ⁵ Offsetting Top Tray: 500 sheets Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position stapling) 11 x 17 in., 8.5 x 14 in./A3 or 200 sets (single-position staple) 8.5 x 11 in./A4 Sizes 3.9 x 5.8 in to 12.6 x 19.2 in/100 x 148 mm x 320 x 488 mm for top tray | |
| Sizes Letter = 8.5 x 11 in./A4 SEF Legal = 8.5 x 14 in./B4 SEF Tabloid = 11 x 17 in./A3 SEF | STREET |
| Legal – 8.5 x 14 in./B4 SEF Tabloid – 11 x 17 in./A3 SEF Saddle-Stitch Stapling 2-15 sheets/8-60 page booklet 16 lb. bond to 67 lb. bond/60 to 256 gsm 1-15 sheets/unstapled 18 lb. bond to 28 lb. bond/60 to 105 gsm Business Ready (BR) Finisher (Optional) (Requires Horizontal Transport Kit) Capacity ⁵ Offsetting Top Tray: 500 sheets Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position stapling) 11 x 17 in., 8.5 x 14 in./A3 or 200 sets (single-position staple) 8.5 x 11 in./A4 Sizes 3.9 x 5.8 in to 12.6 x 19.2 in/100 x 148 mm x 320 x 488 mm for top tray | |
| Score/Crease 1-15 sheets/unstapled 18 lb. bond to 28 lb. bond/60 to 105 gsm Business Ready (BR) Finisher (Optional) (Requires Horizontal Transport Kit) Capacity ⁵ Offsetting Top Tray: 500 sheets Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position stapling) 11 x 17 in., 8.5 x 14 in./A3 or 200 sets (single-position staple) 8.5 x 11 in./A4 Sizes 3,9 x 5.8 in to 12.6 x 19.2 in/100 x 148 mm x 320 x 488 mm for top tray | |
| Business Ready (BR) Finisher (Optional) (Requires Horizontal Transport Kit) Capacity ⁵ Offsetting Top Tray: 500 sheets Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position stapling) 11 x 17 in., 8.5 x 14 in./A3 or 200 sets (single-position staple) 8.5 x 11 in./A4 Sizes 3,9 x 5.8 in to 12.6 x 19.2 in/100 x 148 mm x 320 x 488 mm for top tray | |
| Capacity ⁵ Offsetting Top Tray: 500 sheets Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position stapling) 11 x 17 in., 8.5 x 14 in./A3 or 200 sets (single-position staple) 8.5 x 11 in./A4 Sizes 3,9 x 5.8 in to 12.6 x 19.2 in/100 x 148 mm x 320 x 488 mm for top tray | - P. V. |
| Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position stapling) 11 x 17 in., 8.5 x 14 in./A3 or 200 sets (single-position staple) 8.5 x 11 in./A4 Sizes 3,9 x 5.8 in to 12.6 x 19.2 in/100 x 148 mm x 320 x 488 mm for top tray | |
| Sizes 3.9 x 5.8 in to 12.6 x 19.2 in/100 x 148 mm x 320 x 488 mm for top tray | |
| 7.25 x 10.5 in. to 12.6 x 19 in./182 x 203 mm to 320 x 488 mm for stocking 7.25 x 10.5 in. to 11 x 17 in./185 to A3 for stapling | |
| Weights 16 lb. bond to 110 lb. cover/52 to 300 gsm | |
| Stapling Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb./90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported | |
| Hole Punch North America: 2/3-hole punch Europe: 2/4-hole punch Optional: 4-hole "Swedish" punch | |
| BR Booklet Maker Finisher (Optional) (Requires Horizontal Transport Kit) | WE WAY |
| Capacity ⁵ Offsetting Top Tray: 500 sheets of 8.5 x 11 In./A4 unstapled Stacking Stapling Tray: 1,500 sheets of 8.5 x 11 in./11 x 17 in./A4/A3 unstapled or 200 stapled sets of 8.5 x 11 in./A4 (single-position stapling or dual or 4-position stapling) or 100 stapled sets of 11 x 17 in./A3 | |
| 3.9 x 5.8 in to 12.6 x 19.2 in/100 x 148 mm x 320 x 488 mm for top tray 7.25 x 10.5 in. to 12.6 x 19 in./182 x 203 mm to 320 x 488 mm for stacking 7.25 x 10.5 in. to 11 x 17 in./B5 to A3 for stapling | |
| Weights 16 lb. bond to 110 lb. cover/52 to 300 gsm | |
| Stapling Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb./90 gsm Letter, Legal, Tabloid, A3. A4, B4 and B5 sizes supported | |
| Hole Punch Europe: 2/4-hole punch Optional: 4-hole "Swedish" punch | |
| Booklet Maker Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 gsm coated or 5 sheets at 177 to 220 gsm coated) Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4 supported | |

Types

C-fold, Z-fold and Z-half-fold

Capacity⁵

40 sheets

C-fold and Z-fold: Letter -8.5×11 in./A4 SEF only

Z-hatf-fold: Tabloid - 11 x 17 in./A3 only

Weights

16 lb. to 24 lb. bond/64 to 90 gsm

Output Trays

Envelope Tray: C-fold, Z-fold and Tri-fold Stacker Tray or Top Tray: Z-half-fold

Capacity⁵

50-sheet stapling

5,000 staples

Requires separate power outlet

First-Copy-Out Time (from platen/warmed up Color/Black-and-White)

As fast as 6.1 seconds/ As fast as 4.5 seconds

As fast as 5.5 seconds/ As fast as 4.4 seconds

As fast as 4.7 seconds/ As fast as 3.7 seconds

As fast as 4.0 seconds/ As fast as 3.2 seconds

Sides (input:output)

1-1, 1-2, 2-2, 2-1

Quantity

1 to 9,999

Resolution (max)

Up to 600 x 600 dpi

Reduction/Enlargement

Variable zoom from 25% to 400% in 1% increments

Concurrency

Program-ahead to allow job to be queued while initial job is processed (Copy, Print, Fax and Scan)

Copy Features

Annotation and Bates™ stamping (with color capability and font size adjustment)

Authentication for Services (I.e., Color Copy)

Auto Paper Select

Auto Reduction & Enlargement (To fit selected paper size)

Auto Tray Switching
Automatic 2-sided/Duplex Booklet Creation

Build Job (Enables page-level programming and also lets you proof each section or delete last section as the job is built)

Covers (Front only, front and back, back only, printed inside and out: Blank or Printed)

Dividers (blank)

Edge Erase

Features Help (Intuitive text and graphic descriptions)

ID Card Copy

Image Quality Adjustments

Image Shift (with Auto Center option) Invert Image (negative or mirror image)

Large Job Interrupt

Multi-up (up to 15 columns by 15 rows)

Sample Set Save Job Settings Single Color Stapling Transparencies

| Resolution (up to) | 1200 x 2400 dpi |
|-----------------------------|--|
| Print Features | Application Defaults Banner Sheet Enable/Disable Custom Color Options (Color By Words) Bi-directional Real-time Status Cover Selection Del in s e ifi ti e) er P is ins Image Options (Toner Saver, Resolution (Standard, Enhanced, High) ob n i ion int ID or n er, rint ID in a ins fir a e on a a LAN Fax (requires optional Fax Kit) Layout/Watermark N-up (up to 16 pages per sheet) Booklet Layout Long Sheet/Banner Finishing Fit to New Paper Size Hold All Jobs Paper Selection by Attribute Sample Set Saved Job (color jobs can be printed as monochrome) Secure Print with Timed Deletion Special Pages (exception page programming: covers, inserts, exception pages) Store and Recall Driver Settings Sustainability Features (Xerox* Earth Smart Settings, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Set, Hold All Jobs) Two-sided Printing (as default) Print From Cloud Repositories (Dropbox, OneDrive, and Google Drive) |
| Print from USB | Allows walk-up printing from Type A USB port on front panel Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, PS, PCL Color jobs can be printed as black-and-white |
| Operating Systems | Windows Server 2008 SP2 (32- and 64-bit) Windows Server 2012 and R2 (64-bit) Windows Server 2016 (64-bit) Windows Server 2019 (64-bit) Windows Server 2019 (64-bit) Windows Server 2019 (64-bit) Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 10 (31- and 64-bit) |
| Network Pratocols | TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD Microsoft Windows Networking over IP Bonjour®/AirPrint® IPv6 Most protocols not in use can be disabled |
| Font Capability | PCL: 93 scalable fonts, line printer and bitmap font (including Cyrillic font support) PostScript 3: 173 Type 1 fonts, 2 Multiple Moster fonts |
| Xerox® Global Print Driver® | A truly universal print driver that lets 1T administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls and simplifying print services management. |
| Xerox® Pull Print Driver | Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others. |
| Features | Services supported: Fax, Internet Fax, Email, Scan to Maximum contacts: 5,000 Contacts: Supports 1 or more destinations Favorites for quick access of all services supported |

Concurrency Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs (priority is for return of scanned originals and printing

concurrent jobs)

Input Speed (up to) 82 ppm black-and-white and color (simplex)
141 ipm black-and-white and color (duplex)

135 ppm black-and-white and color (simplex) 270 ipm black-and-white and

color (duplex)

Resolution

72 x 72 dpi to 600 x 600 dpi

Bit Depth

1-bit (black-and-white), 8-bit (grayscale), 24-bit (color)

Maximum Scan Area

11 x 17 in./A3

Scan Template Management Support 250 scan templates

Create Xerox® CentreWare® IS sc n m

s n sar vi devi e ni o er utfncti n printer

ainse tn

Network Protocols

SFTP, FTP, SMB, HTTP, HTTPS

File Compression

Color TIFF (TIFF 6.0 or TTN2 with JPEG, LZW)

Black-and-white TIFF (G3MH, G4 MMR compression – single or multiple pages)

e habeP C and M C. MRC)) Linearized PDF/PDF/A H, G4 MMR, JBIG 2 Huff n, JBIG rithmetic C pressi n, Deflate (f r bl ck-an -white and w th n

Document Management Fields (Metadata) Features only available in Network Scan to File Templates:

• 1 to 6 user p grammabl adat filds pe network scant file t mplat s and unlited fild with the t mplate – M adota field consists of filds

name, default value an other c infigurations

Customized fi lds viewed on user interface for ariab! data input

Scan Features

Mixed Size Originals Scan Build Job

Scan Preview

Compression Quality/File Size Control

Original Type (Photo and Text, Photo, Text, Map, Newspaper/Magazine)

Auto Background and Shadow Suppression Size for Size (for mixed size originals) TWAIN Support/WIA 2.0 Support

Bound Originals Edge Erase

Reduction/Enlargement

Single Touch Scan buttons (up to 10)

Scan to Email (Standard)

Scan Features • Email signatures (6 lines each of 128 character max), email m ssag b dy (us r con gurab), email Embedded Web S rver confirmation sheet ptions

Scan to Email S/MIME Encryption
 Email signing (requires Smart Card option)

Auto send to self

Directory Access Address list via LDAP (Windows Active Directory, Exchange, Notes, Domino), Device Address Book

Scan To

Standard Features Scan to USB

Scan to Network Folder (using Secure FTP/HTTP/HTTPS)

Scan to Home

Scan to Network (using Secure FTP/HTTP/HTTPS)

Scan to Email

Scan to PC/Server Client (SMB or FTP)

Scan to Mailbox

Optional Features Native Scan to Cloud Repositories (Dropbox, OneDrive, and Google Drive)³

Workflow Scanning (Optional features)

Scanning Software Autostore v7

ecopy ShareScan v5.2 eCopy ScanStation v5.2

Scanning Apps and Xerox App Gallery Scan to/from: D opbox, Google Drive, Mic osoft OneDri e, Micros ft Office 365, B x, Xerox® Workplace Mobile App (iOS/Android)

See the full list of apps available in the Xerox App Gallery: xerox.com/AppGallery

| Security | AltaLink® C8130 | AltaLink® C8135 | AltaLink® C8145 | AltaLink® C8155 | AltaLink® C8170 |
|---|--|--|--|---|-----------------|
| Security Features | Expanded Authenticatin Network authenticatin Windows server 2012 Local Authentication I Smart Card authentication I Smart Card authentication I Digitally signed PDF (i Encrypted and auther Encrypted/Password P Secure Print (up to 10 Immediate Image Ov On Demand Image Ov On Demand Image Ov Immediate Image Ov On Demand Image Ov On On Demand Image Ov On Demand Image Ov On On Demand Image Ov On | on on to access device and/or device), NDS, LDAP authentication (internal database) action – 144k CAC/PIV Card Supplement and on the server for Scar protected PDF (when using Email digit PIN or Network Authentication to SMTP server for Scar grant of the service of the server for Scar and Disk Encryption, TLS 1.1/1.2/10 or Network Authenticate Disk Encryption, TLS 1.1/1.2/10 or Network credentials reper service irred to access Print and Print February Service irred to access | e services via Kerberos (UNIX/Wi boort (2048 bit certificate key)/.NE ication) to Email I and Network Scan Templates or ation) ing approved algorithms ¹¹ icludes sanitation of unused area 1.3, IPPS, HTTPS, SFTP, SNMPv3 atures (e.g., color access, or time is security settings): it, Recipient Group Preferences the Download e Activation e Device Settings ynchronization Time atically Send Diagnostic Informate e | ndows Server 2008), SMB (Windo | ws Server 2008, |
| | Port disablement includi Audit Log Hide Print Job Names Cisco® Identity Services Security Information an Full System Common Cr | Engine (ISE) compatible | apport for McAfee® Enterprise Sec D Pro in Profile for ard o | curity Manager, LogRhythm and S evice v 0 (HCD-PP v1.0)* | plunk³ |
| Xerox [®] Integrated RFID Card Reader (Optional Kit) | | ost industry security cards provid | 4.4 | edded multifunction printer card i | readers in |

| Network Server Fax Features | |
|------------------------------|--|
| Compatibility | ITU (CCITT) group 3; Various Xerox Business Innovation Partner Solutions |
| Maximum Scan Area | 11 x 17 in/A3 |
| Fax Send Features | One- or Two-sided Scanning (up to 11 x 17 in./A3) Add to Send List (200 numbers maximum) Build Job, Favorites, Delay Send (specific time) Original Type (photo, text or photo and text) |
| Fax Print Features | One- or Two-sided Printing, Staple, Secure Print |
| Transmission Resolution | Superfine: 400 x 200 dpl (Scan at 600 x 600 dpl) Fine: 200 x 200 dpl Standard: 200 x 100 dpl |
| Internet Fax Features | |
| Compatibility | Direct print-ready document transmission to remote Internet Fax machines or email clients (SMTP) Reception and automatic printout of documents sent via email from remote Internet Fax machines or email clients |
| Directory Access | Utile he Uniled Addles Book |
| Send/Receive | Send: Multi-page TIFF, PDF, PDF/A Receive: TIFF, MTIFF, PDF, PDF/A, PS, text, PCL, PRN, JPEG |
| Resolution | 72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black-and-white) |
| Network Protocols | SMTP (send), POP3 (receive) |
| Compliance | ITU-T T.37 compliant |
| Walk-up Fax Features (Option | ndi; Customer-Installable – 1 and 2 lines) |
| Compatibility | ITU (CCITT) Group 3 |
| Speed/Modems | One or Two V.34 moderns: 33,600 bps. Less than 4 seconds per page transmission time |
| Compression/Speed | MH/G3, MR/G3, MMR/SG3, JBIG/SG3 |
| Resolution | Walkup Send: Standard: 200 x 100 dpi ine 200 x 00 dpi Superfine: 600 x 600 pi Receive: Accepts all sizes |
| Fax Send Features | LAN Fax (fax from print driver) Auto Fax Transmission Reduction Page-by-page Job Status at the Machine Delay Start, Build Job, Favorites Automatic Memory Resend Automatic Cover Sheets PSTN Fax Batch Send (up to memory capacity) Device Address Book (up to 5,000 contacts) |
| Fax Receive Features | One- or Two-sided Printing Stapled or Unstapled Receive Print Mode – Manual (size, margin, stock, header)/Auto Output Tray Selection Up to 200 Password Protected Mailboxes Secure Receive Receive Timestamp Auto Answer Delay |
| Fax Forward | Forward to Email or SMB Location Fax Forward on Receive Only |
| Fax Reports | Acti ty Dia irec ory, Group ir ct r , T an ission Confi ma ion. Pen ing F , Op ions epor , On D mand Over rit Report, Mailbox Re ort. Broadcast Report |
| Directory Access | iliz t Unified Address Book Group fax available |
| Auto Redial | Up to 14 attempts (per country requirements) 1 to 25 minute intervals |
| Auto Resend | Up to 5 attempts |

| Device Management | · · · · · · · · · · · · · · · · · · · | |
|--|---|--|
| Administrative Protocols | DHCP, BOOTP, SNMP, SLP® v2, HTTP, HTTPS, DHCP Autonet, TLS, NTP, DNS, SMB, SMTP/POP3, WSD, LDAP, Multicast DNS | |
| Management Support | SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213) Host R so rces B RF 2790, Printer MIB RFC 38 P - maging-System-Power MI , o r ion rc e tr tor Configuratio Wa h og | |
| Xerox ^o CentreWare ^o Web | A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running on Windows, UNIX or any other operating system: • Works with any SNMP-managed printer from any manufacturer • e ot o figu tion o SNMP v • Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management • Requires Windows 7 and Internet Explorer 6.0 and higher • Auto-detect Xerox® CentreWare® b ser er and d n oad on rains fills for o chless re o einst ill | |
| Xerox [©] Device Manager | Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single too to 1 to 1 print ues and configure, manage, manitor and re ort on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: • Device monitoring and troubleshooting • Remote configuration of SNMP v3 • Extensive reporting and discovery of new devices • Usage collection, chargeback and billing capabilities • Auto-detect Xerox® Device Manager server and download configurations files for touchless remote install | |
| Xerox® Workplace Cloud | Remote management to set and audit device configuration data with Xerox® Workplace Cloud, eliminating the need for an on-site server. | |
| Fleet Orchestrator | Fleet Orchestrator feature offers the ability to a eate a group of devices that share information with each other via a secure peer-to-peer connection. The following data can be shared: Software update files, clone files, and 1-Touch App files. | |
| Novell NDPS/NEPS | Server gateway application: centralized management tool. | |
| Xerox® Device Types for SAP Environment | Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Program, provides seamless connectivity between SAP systems and your Xerox® Printers and Multifunction Printers. As an SAP customer, you benefit from having SAP-certified Xerox® Device types available right from SAP's online delivery model. SAP-certified device types for Xerox® Printers and Multifunction Printers are available to download. office.xerox.com/Software-Solutions | |
| Xerax® Device Types for SAP R/3 Intelligent Barcode Utility (aptional) | Provides built-in process intelligence that allows the printing of barcodes on any app opriately configured PostScript printe in specific ve sions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Center Barcode Fonts. Information available at office.xerox.com/Software-Solutions | |
| Xerox [®] Barcode Pro PS (optional) | Enables intelligent PostScript printing on Xerox® Multifunction Printers by storing Xerox® Software, as well as the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at office.xerox.com/Software-Solutions | |
| Xerox® Embedded Web Serve | er — Integrated Device Web Pages Provided by the Device | |
| Device Status | Web server embedded in Network Controller: Tray status/cantents Consumables status Alerts Remote Control Panel | |
| Job Submission | Print-ready files: PS, PCL, TIFF, PDF, JPG, TXT, PRN Output feature selection (2-sided, output color, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint) | |
| Device Administration | Allows simple, remote installation setting of configuration options and management of the device, Fleet Orchestrator | |
| Browsers | Internet Explorer 10.x, 11.x Safari 10.x, 11.x Mazilla Firefox 45.x through 53.x Opera 25x through 53.x Chrome 48.x through 72.x | |
| Support | Install print/scan drivers and online support available via support.xerox.com | |
| Languages Supported | International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese, Arabic | |
| Remote Services | | |
| Xerox® Automatic Meter Readings (AMR) | Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® Device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time. | |
| Xerox® Automatic Supplies Replenishment (ASR) | Automatically orders supplies for Xerox ³ output devices based on actual usage, eliminating the need to manually manage supplies inventory. | |

lerox® Standard Accounting (Standard) Tracking Copy, Print, Fax, Scan and Email usage Up to 2,497 User Accounts (User ID) Accounting Up to 500 General Accounts (Client) Up to 498 Group accounts (Department) Administrator can manage the feature via the Web User Interface or device control panel in tools. mi tra o h s th ability o import or expo User control Grop control Grop and User Limit s via it dusrys and r CSV file. **Features**

Accounting Options — Network Accounting (Allows central server to manage all accounting)

Enhanced network accounting with up-to-the-minute data on how the system is being used
 Comprehensive management and enterprise-scale tracking and reporting of device usage of copy, print, scan and server fax
 Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com
 Security enhancements with the addition of HTTPS protocol support
 Device requests account authentication from third-party server enabling larger databases of users and accounts

Accept Authentication Login at control panel and pass to third-party Networking Account
 Interface with third-party accounting terminal for accounting user interface

Xerox[®] EX-c C8100 Print Server Powered by Fiery[®] (Optional)

AMD® GX-424CC processor, 2.4 GHz, Quad-Core, 2M cache Processor

Memory (ESS)

System Disk 500 GB HDD

Page Description Language PostScript v 3020

Fiery Command WorkStation for Mac and Windows clients (customer provided) Features

Fiery drivers for Mac and Windows

Job Preview Job Presets Image Enhance

Spool-RIP-Print simultaneously

Automatic two-sided printing

N-up

Watermarks Calibration

PANTONE® Color Enabled

Exper Color Set ings: Prollle, Rendering and Simula ion Fi y eeForm C eate to r ate personaliz d files for fre Booklet Maker - booklet wizard to create booklets

Standard support for long sheet banners

Pritfom USB flash dive

Secure Erase

Encryption of critical information

Secure Printing User Authentication Access Controls PostScript Security Port Blocking IP Filtering

Digitally Signed Software Updates

Integrates with common cost accounting software, Xerox® Standard Accounting, Xerox® App Gallery Apps, and more

10Base-T/100Base-TX/1000Base-T Ethernet Connectivity

Fiery Op ons Bundle (Fey S On, Au o Tapig, H F des, Virua Pinrs), Fiey HtF des/Virual Piters Fr StO Fe Co Pr r Suite Optional

w/EFI ES-2000 Spectrophotometer, Network Switch to connect both printer and Fiery Server to network

| Supplies | Description | Yield |
|--|---|--|
| Toner Cartridge ⁷ | Black Cyan Magenta Yellow | 59,000 pages 28,000 pages 28,000 pages 28,000 pages |
| Transfer Belt Cleaner | 1 Assembly | 160,000 pages |
| Second Bias Transfer Roll | 1 Assembly | 200,000 pages |
| Staple Cartridges | For BR Finisher, Integrated Office Finisher, Office Finisher and Convenience Stapler (1 cartridge per carton) | 5,000 each cartridge |
| | For BR Booklet Maker (1 cartridge per carton) | 5,000 each cartridge |
| | For Office Finisher Bookle er c t idges er ca t | 2,000 each cartridge |
| αel | For I egrite Official refice Finis , Finis er n Conjeniencit le relis per rtin | , e refil |
| Fan Filter | 1 Assembly (AltaLink® C8170) | 500,000 pages |
| Xerox® Smart Kit® | | |
| Drum Cartridge ⁹ | 1 Cartridge per Color | 180,000 pages |
| Waste Toner Container w/o Suction Filter ¹⁰ | 1 Cartridge (AltaLink® C8130/35/45/55) | 69,000 pages |
| Waste Toner Container with Suction Filter ¹⁰ | 1 Cartridge (AltaLink® C8170) | 69,000 pages |

 $Return\ spent\ imaging\ supplies\ through\ the\ Xerox\ Green\ World\ Alliance\ collection/reuse/recycling\ program.$ For more information, visit www.xerox.com/About-Xerox/Recycling.

For more information, visit us at w.x x.com/Offi e.

Declared in accordance with ISO/IEC 24734.

Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

Available post-founch via software update.

Not available in all geographies.

Paper capacities are based on 20 lb./75 gsm stock; capacities will vary with different weight stocks.

Sold separately in some geographies.

Average standard pages. Declared in accordance with ISO/IEC 19798. Toner yield can vary due to many foctors, including but not limited to, image area coverage, image content, medio size, medio orientation, run mode, application types, monthly print volumes and image quality set-points.

de e 1 in; e tifica ion ex et din Q 2 21

Average drun yield is based on a run length of 5 pages of 8.5 x 11 in/A4 LEF pages, with split of 35% color/65% black-and-white pages.

Waste Toner Container yield will vary depending on type of image, area coverage % and Job run length.